
**BK1614-RS** **Drawn cup needle roller bearing closed end**

Drawn cup needle roller bearings with closed end BK...-RS, lip seal on one side

Technical information**Your current product variant**

Lubricant	L271	Grease (L271/customer specific)
Lubrication hole	Without	
Coating	Without	
Sealing	RS	Contact seal on one sides

Main Dimensions & Performance Data

F_w	16 mm	Under roller diameter
D	22 mm	Outside diameter
C	14 mm	Width, outer ring
C_r	7.600 N	Basic dynamic load rating, radial
C_{0r}	9.700 N	Basic static load rating, radial
C_{ur}	1.180 N	Fatigue load limit, radial
n_G Grease	9.300 1/min	Limiting speed for grease lubrication
n_G	9.300 1/min	Limiting speed
m	15 g	Weight

Dimensions

r_{min}	0,8 mm	Minimum chamfer dimension
$C_{t min}$	11,3 mm	Minimum width to base of drawn cup with closed end



Temperature range

T _{min}	-20 °C	Operating temperature min.
T _{max}	100 °C	Operating temperature max.

Additional information

IR12X16X13-XL	Suitable inner rings IR
---------------	-------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Sealed on one side
-  Small design envelope